

Gruppo Specifications



SRAM APEX	Shifter	Rear Derailleur	Crankset	Bottom Bracket	Front Derailleur	Brakeset	Cassette	Chain
Technology	DoubleTap® / ZeroLoss™ on the front / Reach adjust	Exact Actuation™ / WiFLi technology	PowerGlide™ Chainrings	GXP	WiFLi technology / ZeroLoss™ Trim	Skeletonized Dual Pivot	PowerGlide™ / WiFLi technology	PowerLock®
Speeds	10	10	2	NA	2	NA	10	10
Weight	344g	Short Cage - 200g Mid Cage - 210g	890g (w/ BB)	115g (GXP)	89g Braze-On	308g	299g (11-32) 250g (11-23)	277g (1050 / 114 Links)
Material // Finish	Forged Brake Lever / Cast Shift Lever // Jet Black Gloss	Alloy outer cage / Steel inner cage // Jet Black Gloss	Aluminum // Jet Black Gloss	CNC Alloy Cups // Jet Black Gloss	Aluminum / Steel // Jet Black Gloss	Cold Forged / Stainless Steel // Jet Black Gloss	Forged Alloy Spider / Heat-Treated Steel // Chrome Plated	Heat-Treated Steel // Black
Compatibility	SRAM Red, SRAM Force, SRAM Rival, and SRAM Apex Front and Rear Derailleurs	Short - Max Tooth 28T Mid - Max Tooth 32T	GXP 53/39, 52/38, 52/36, 50/36, 50/34, 46/38	SRAM Red, SRAM Force, SRAM Rival, and SRAM Apex Cranksets	55/42, 54/42, 53/39, 52/38, 52/36, 50/36, 50/34, 46/38 Max Tooth 16T	DoubleTap® Controls	11-32, 11-28, 11-26, 11-23T	SRAM Red, SRAM Force, SRAM Rival, SRAM Apex and industry standard 10 spd systems

SRAM
APEX™